

CEMENT TILES

SQUARE TILES



8 x 8 x 0.4 inch
20 x 20 x 1.2 cm

RECTANGLE TILES



2 x 12 x 0.6 inch
5 x 30 x 1.6 cm



4 x 8 x 0.4 inch
10 x 20 x 1.2 cm

HEX TILES



9 x 8 x 0.4 inch
10 x 20 x 1.2 cm

Water Absorption	10.7%
Breaking Bending Load	103.7 N
Impact Test	10.7%
Surface Hardness	Pass
Static Coefficient of Friction for Dry Surface	0.96 F _D
Static Coefficient of Friction for Wet Surface	0.79 F _w
Resistance to Surface Abrasion	0.56 g/cm ²

CEMENT TILES

Product Type	Encaustic Cement Tile
Weight / sqm	5.17 lbs / per sqf (8 x 8 x 0.4 inch, 4 x 8 x 0.4 inch) 6.76 lbs / per sqf (2 x 12 x 0.6 inch) 5.64 lbs / per sqf (9 x 8 x 0.4 cm)
Size(s)	8 x 8 x 0.4 inch (20 x 20 x 1.2 cm) 4 x 8 x 0.4 inch (10 x 20 x 1.2 cm) 2 x 12 x 0.6 inch (5 x 30 x 1.6 cm) 9 x 8 x 0.4 inch (10 x 20 x 1.2 cm)
Slippery Rate	R11
Surface	Honed Finish
Usage	Indoor / Outdoor
Application Area	Floors / Walls
Material	Cement
Sealant	Stonetech Impregnator Pro Sealer or Miracle 511 Porous Plus Apply before and after the installation
Grout	As specified by the architect
Maintenance and Cleaning	Clean with pH natural floor cleaners